

AC-DC Adapter

PD 65W / ADP-65KE B

ADP-65KE B

Highlights & Features

- Meet efficiency DoE Level VI & CoC Tier 2
- No load power consumption < 0.075 W
- AC-DC adapter
- Fully enclosed plastic case
- Protection: short circuit / over voltage / over current / over temperature



Safety Standards



CB Certified for worldwide use

Model Number:	ADP-65KE BY
Unit Weight:	210g ±5%
Dimensions (L×W×H):	90 x 51 x 28.5 mm
Remark:	The AC cable is detachable.

General Description

The ADP Series of AC-DC wall mount adapter in compact size. ADP-65KE BY meet the DoE Level VI and CoC Tier 2 energy efficiency requirements and the extremely low no-load power consumption below 0.075 W. The series conform to major international safety standards according to IEC/EN/UL 62368-1 approval for ITE. In addition, they also meet the EMI approvals to EN 55032 class B.

Model Information

Model Number	Input Voltage Range	Efficiency Level	Rated Output
ADP-65KE BY	90-264 Vac	Level VI & CoC Tier2	5V/3A ; 9V/3A ; 12V/3A ; 15V/3A ; 20V/3.25 ^a

Model Numbering

ADP -	65	K	E	B	Y
Adapter or Charger	Wattage	Series Code	Adapter	AC Plug Type B:C6	

AC-DC Adapter

PD 65W / ADP-65KE B

Specifications

Input Ratings / Characteristics

Nominal Input Voltage	100-240 Vac
Input Voltage Range	90-264 Vac
Nominal Input Frequency	50-60 Hz
Input Frequency Range	47-63 Hz
Input Current (max) @ 100 Vac	1.7 A
Average Efficiency (min)	5V \geq 81.84% ; 9V \geq 87.30% ; 12V \geq 88.30% ; 15V \geq 88.85% ; 20V \geq 89.00% @ 115 Vac & 230 Vac
No Load Power Consumption (max)	5V/0.075 W/ @ 115 Vac & 230 Vac
Inrush Current @ Cold start	Fuse I ² t < 22%
Leakage Current (max) @ 240 Vac/50 Hz	50 uA

Output Ratings / Characteristics

Nominal Output Voltage	5V/9V/12V/15V/20V
Output Current	3A @ 5V/9V/12V/15V ; 3.25A @ 20V
Output Power	65W
Line Regulation	\pm 5%
Load Regulation	\pm 5%
PARD* (20 MHz) @ 25°C	< 180 mV pk-pk (5V)
	< 210 mV pk-pk (9V)
	< 250 mV pk-pk (12V)
	< 300 mV pk-pk (15V)
	< 300 mV pk-pk (20V)
Turn on delay Time	< 3 S @ 100~240 Vac, 5V only
Rise Time	< 40 ms @ 100~240 Vac, 100% load, 5V only
Hold-up Time	> 5 ms @ 115 Vac, 100% load, 20V only
Peak Load @ 25°C	> 17V @ 180% Load, 2ms, 100~240 Vac (20V)
	> 13V @ 180% Load, 2ms, 100~240 Vac (15V)

*PARD is measured with an AC coupling mode, and in parallel with 0.1uF ceramic capacitor & 47uF electrolytic capacitor.

Mechanical

Case	PC	
Dimensions (L x W x H)	90x 51 x 28.5 mm	
Unit Weight	210g \pm 5%	
Indicator	N/A	
Cooling System	Convection	
Output Cable Specification	Connector	Type-C
	Length	1500 \pm 30mm
Input Socket	C6	

AC-DC Adapter

PD 65W / ADP-65KE B

Environment

Surrounding Temperature	Operating	0°C to +35°C
	Storage	-30°C to +80°C
Power De-Rating		N/A
Operating Humidity		5%-90% RH (non-condensing)
Operating Altitude		5,000 meters (16,400 feet)
Ball Impact Test		Test height 130 cm, 1 sample 1 time, Steel Ball 500 g, Concrete floor
Drop Test		Test height 100 cm, 6 face for each sample, concrete floor Function test pass after drop test
Shock Test (Non-Operating)		50 G, 11 ms, 1 shock for each direction
Vibration (Non-Operating)		5-500 Hz, 2.09 Grms, 20 mins, one cycle for each three axis

Protections

Overvoltage (max)	<8.5V @ 5V ; <15V @ 9V ; <19V @ 12V ; <22V @ 15V ; <28V @ 20V, Latch mode
Overload / Overcurrent (max)	3.05~3.9A @ 5V ; 3.05~3.9A @ 9V ; 2.55~3.4A @ 12V ; 2.05~2.9A @ 15V ; 1.55~2.4A @ 20V, Latch mode
Over Temperature	Latch mode
Short Circuit	Latch mode
Pollution Degree	2
Protection Against Shock	Class I

Reliability Data

MTBF	> 100,000 hrs. at Input: 115 Vac, Output: 100% load, Ta: 25°C
Expected Cap Life Time @ 25°C	8736 hours @100% load, 100Vac
Case Temperature Rise	Top case< 45°C, Bottom case< 50°C @ 100Vac, Output: 100% Load, Ta: 25°C

AC-DC Adapter

PD 65W / ADP-65KE B

Safety Standards / Directives

Electrical Safety		IEC/EN 62368-1, 60950
		BSMI CNS 13438, 14336-1, 15663
		PSE J62368-1, J55032, J3000
		UL 62368-1, CSA 62368-1
		PSB IEC 62368-1:2014, 60950-1:2005+A1:2009+A2:2013
CE/UKCA		Comply with EMC Directive 2014/30/EU, the Low Voltage Directive 2014/35/EU, RoHS Directive 2011/65/EU+ (EU) 2020/659 and Commission Regulation (EU) 2019/1782, ErP Directive
Galvanic Isolation	I/P to O/P	3000 Vac

EMC

EMC / Emissions	EN 55032	Criteria Class B
Harmonic Current Emissions	IEC 61000-3-2	The power consumption of EUT is less than 75W and no limits apply
Voltage Flicker	IEC 61000-3-3	
Electrostatic Discharge	IEC 61000-4-2	Air Discharge: 15 kV, Criteria A Contact Discharge: 8 kV, Criteria A
Radio Frequency Electromagnetic Field	IEC 61000-4-3	Criteria A 80 MHz – 1 GHz, 3 V/m, 80% AM (1 KHz)
Electrical Fast Transient	IEC 61000-4-4	Level 3 Criteria B
Surge	IEC 61000-4-5	Level 3 Criteria A Common Mode: 2 kV Differential Mode: 1 kV
Radio Frequency Common Mode	IEC 61000-4-6	Criteria A 150 kHz – 10 MHz, 3 V, 80% AM (1 KHz) 10 MHz – 30 MHz, 3V-1V, 80% AM (1 KHz) 30 MHz – 80 MHz, 1V, 80% AM (1 KHz)
Power Frequency Magnetic Fields	IEC 61000-4-8	Criteria A 1 A/m, 50Hz
Voltage Dips	IEC 61000-4-11	Voltage dips 70% residual voltage, 25 periods (Criterion C) < 5% residual voltage, 0.5 periods (Criterion B) Voltage short interruptions < 5% residual voltage, 250 periods (Criterion C)

1) Criteria A: Normal performance within the specification limits

2) Criteria B: Output out of regulation, or shuts down during test. Automatically restore to normal operation after test.

3) Criteria C: PSU shuts down during test, but need operator to reset.

4) Asymmetrical: Common mode (Line to earth)


5) Symmetrical: Differential mode (Line to line)

AC-DC Adapter

PD 65W / ADP-65KE B

Dimensions (ADP-65KE BY)

L x W x H: 90 x 51 x 28.5 mm




ITEM	PART NAME	COLOR
①	COVER	BLACK
②	CHASSIS	BLACK
③	AC INLET	BLACK
④	DC CABLE	BLACK
⑤	LABEL	BLACK

AC-DC Adapter

PD 65W / ADP-65KE B

Engineering Data

Output Load De-rating V.S. Surrounding Air Temperature



Others

Attention

Delta provides all information in the datasheets on an “AS IS” basis and does not offer any kind of warranty through the information for using the product. In the event of any discrepancy between the information in the catalog and datasheets, the datasheets shall prevail (please refer to PSU.deltaww.com for the latest datasheets information). Delta shall have no liability of indemnification for any claim or action arising from any error for the provided information in the datasheets. Customer shall take its responsibility for evaluation of using the product before placing an order with Delta.

Delta reserves the right to make changes to the information described in the datasheets without notice.

Manufacturer and Authorized Representatives Information

Manufacturer

China
 Delta Electronics (Jiangsu) Ltd.
 No.1688, Jiangxing East Rd., Wujiang Economic and Technological Development Zone, Suzhou City, Jiangsu Province, P.R.C.

Authorized Representatives

The Netherlands
 Delta Greentech (Netherlands) B.V.
 Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands

United Kingdom
 Delta Electronics Europe Limited
 1 Redwood Court, Peel Park Campus,
 East Kilbride, Glasgow, G74 5PF, United Kingdom

